

UTILITY LT-A750XP



KINGQUAD 750 POWER STEERING

When the rain comes down, the wind blows hard and you've got a tight deadline to meet, you need the best tool for the job.

That's why we've worked hard to build the best ATV for your business. The KingQuad 750 has the practical features and reassuring power for everything, from blasting across the fields, to towing your livestock trailer up, over and down even the trickiest of hill-paths.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	2115mm
Overall width:	1210mm
Overall height:	1285mm
Ground clearance:	260mm
Seat height:	920mm
Kerb Mass:	307kg
Fuel capacity:	17.5litres

ENGINE SPECIFICATIONS

Engine capacity:	722cc
Engine:	4-stroke, single cylinder, DOHC, 4-valve
Bore:	104mm x 85mm
Compression ratio:	10.0:1
Lubrication:	Wet sump
Ignition:	Electronic Ignition (CDI)
Fuel system:	Fuel injection
Starter:	Electric
Transmission:	Automatic x 2-speed with reverse and front diff-locked 4WD
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, oil-damped. Spring preload, 5 way adjustable
Rear suspension:	Independent, double wishbone, oil-damped. Spring preload, 5 way adjustable
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Sealed oil-bathed multi-disc
Front tyres:	AT25 x 8-12, tubeless
Rear tyres:	AT25 x 10-12, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**



UTILITY LT-A500XP



KINGQUAD 500 POWER STEERING

As you battle the relentless succession of tasks, the winter darkness is already closing in and the cattle are yet to be moved inside, reliability is a necessity.

All the industry-leading features in an even more economical package, the KingQuad 500 won't let you down. The 500 exceeds the demand for performance and economy, a powerful 493cc engine, efficient fuel injection and electric power steering will tow, transport, traverse and tackle everything thrown at it.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	2165mm
Overall width:	1250mm
Overall height:	1285mm
Ground clearance:	260mm
Seat height:	920mm
Kerb Mass:	302kg
Fuel capacity:	17.5litres

ENGINE SPECIFICATIONS

Engine capacity:	493cc
Engine:	4-stroke, single cylinder, SOHC, 4 valve
Bore:	87.5mm x 82mm
Compression ratio:	10.0:1
Lubrication:	Wet sump
Ignition:	Electronic Ignition (CDI)
Fuel system:	Fuel injection
Starter:	Electric
Transmission:	Automatic x 2-speed with reverse and front diff-locked 4WD
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, oil-damped. Spring preloaded, 5 way adjustable
Rear suspension:	Independent, double wishbone, oil-damped. Spring preloaded, 5 way adjustable
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Sealed oil-bathed multi-disc
Front tyres:	AT25 x 8-12, tubeless
Rear tyres:	AT25 x 10-12, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**



Way of Life!

UTILITY LT-A500X



KINGQUAD 500

As you battle the relentless succession of tasks, the winter darkness is already closing in and the cattle are yet to be moved inside, reliability is a necessity.

All the industry-leading features in an even more economical package, the KingQuad 500 won't let you down. The 500 exceeds the demand for performance and economy, a powerful 493cc engine and efficient fuel injection will tow, transport, traverse and tackle everything thrown at it.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	2135mm
Overall width:	1250mm
Overall height:	1245mm
Ground clearance:	260mm
Seat height:	920mm
Kerb Mass:	307kg
Fuel capacity:	17.5litres

ENGINE SPECIFICATIONS

Engine capacity:	493cc
Engine:	4-stroke, single cylinder, SOHC, 4 valve
Bore:	87.5mm x 82mm
Compression ratio:	10.0:1
Lubrication:	Wet Sump
Ignition:	Electronic Ignition (CDI)
Fuel system:	Fuel Injection
Starter:	Electric
Transmission:	Automatic x 2-speed with reverse and front diff-locked 4WD
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, oil-damped. Spring preloaded, 5 way adjustable
Rear suspension:	Independent, double wishbone, oil-damped. Spring preloaded, 5 way adjustable
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Sealed oil-bathed multi-disc
Front tyres:	AT25 x 8-12, tubeless
Rear tyres:	AT25 x 10-12, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**



Way of Life!

UTILITY LT-F400F



KINGQUAD 400 MANUAL

Acres of forestry to maintain, dozens of trees to fell and hundreds of narrow paths to keep clear for walkers, you need to move quickly but safely, control is essential.

Versatile, practical and easy-to-maintain, the KingQuad 400 is ready to muck in. Whether it's carrying feed and lambing equipment on its front and rear cargo racks, or towing livestock in a trailer, the 400 is ready to prove why it's a KingQuad.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	2175mm
Overall width:	1145mm
Overall height:	1200mm
Ground clearance:	235mm
Seat height:	830mm
Kerb Mass:	279kg
Fuel capacity:	16.0litres

ENGINE SPECIFICATIONS

Engine capacity:	376cc
Engine:	4-stroke, air cooled with SACS, SOHC
Bore:	82mm x 71.2mm
Compression ratio:	9.0:1
Lubrication:	Wet sump
Ignition:	Electronic Ignition (CDI)
Fuel system:	Fuel Injection
Starter:	Electric
Transmission:	5 x 2 speed with reverse and selectable 2WD, 4WD
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, coil-sprung, oil-damped. Spring preloaded, 5 way adjustable
Rear suspension:	Swingarm, coil-sprung, oil-damped
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Drum mechanically operated
Front tyres:	AT 25 x 8-12, tubeless
Rear tyres:	AT 25 x 10-12, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**



UTILITY LT-A400F



KINGQUAD 400 AUTO

Acres of forestry to maintain, dozens of trees to fell and hundreds of narrow paths to keep clear for walkers, you need to move quickly but safely, control is essential.

Versatile, practical and easy-to-maintain, the KingQuad 400 is ready to muck in. Whether it's carrying feed and lambing equipment on its front and rear cargo racks, or towing livestock in a trailer, the 400 is ready to prove why it's a KingQuad.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	2175mm
Overall width:	1145mm
Overall height:	1200mm
Ground clearance:	235mm
Seat height:	830mm
Kerb Mass:	285kg
Fuel capacity:	16.0litres

ENGINE SPECIFICATIONS

Engine capacity:	376cc
Engine:	4-stroke, air cooled with SACS, SOHC
Bore:	82mm x 71.2mm
Compression ratio:	9.0:1
Lubrication:	Wet sump
Ignition:	Electronic Ignition (CDI)
Fuel system:	Fuel Injection
Starter:	Electric
Transmission:	Automatic variable ratio with reverse and selectable 2WD/4WD
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, coil-sprung, oil-damped. Spring preloaded, 5 way adjustable
Rear suspension:	Swingarm, coil-sprung, oil-damped
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Drum mechanically operated
Front tyres:	AT 25 x 8-12, tubeless
Rear tyres:	AT 25 x 10-12, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**



UTILITY LT-F250



OZARK 250

The so-called 'quiet season' approaches, but there's still hectares of land to check for fencing repairs, this is no job for a tractor or 4x4.

The Ozark provides a great form of off-road transport, it's tougher than you might expect with a remarkable towing capacity for its size. The 250's compact dimension mean easy manoeuvrability and the 2-wheel drive provides light steering, both of which you'll appreciate after a full day of riding.



Colours available



DIMENSIONS AND WEIGHTS

Overall length:	1870mm
Overall width:	1070mm
Overall height:	1070mm
Ground clearance:	210mm
Seat height:	785mm
Kerb Mass:	199kg
Fuel capacity:	10.6litres

ENGINE SPECIFICATIONS

Engine capacity:	246cc
Engine:	4-stroke, air cooled, SOHC
Bore:	66mm x 72mm
Compression ratio:	9.2:1
Ignition:	Electronic Ignition (CDI)
Fuel system:	Mikuni BS29SS
Starter:	Electric & Recoil
Transmission:	5 x 1 speed with reverse
Drive:	Shaft

CHASSIS SPECIFICATION

Front suspension:	Independent, double wishbone, coil-sprung, oil-damped. Spring preloaded, 5 way adjustable
Rear suspension:	Swingarm, coil-sprung, oil-damped
Front brakes:	Dual discs, hydraulically operated
Rear brakes:	Drum, mechanically operated
Front tyres:	AT22 x 7-11, tubeless
Rear tyres:	AT22 x 10-9, tubeless

**VISIT SUZUKI.CO.UK
OR CALL 0500 011 959**

